



3D Shaker TRDS-602

www.labomate.com | info@labomate.com

Description

3D Shaker TRDS-602 is manageable with a variety of supports and fittings. It has a dual LCD screen that displays the time and speed separately. A DC motor with a maximum speed of 10 to 70 rpm and a working temperature of 5 to 40 °C. Controls the mechanism. It can be used with a timer or in continuous operation mode. It is accomplished by supporting an extremely heavy.

Features:

- The mechanism is performed by a DC motor control
- It has a maximum load-bearing weight capability
- Presented with a double LCD screen, it shows display time and speeds separately
- Making an available variety of brackets and fixtures are available
- It can be used with a timer or in continuous operation mode
- The mechanism is controlled by a DC motor control

Specifications :

Angle of Inclination	10°
Data Access	RS232
Dimension (L×W×H)	425×355×180mm
Maximum Load	5kg
Moisture	0.8
Motor Type	DC motor
Operation Model	Time set, continuous operation
Power	50W
Speed Indicator	LCD
Speed Range	10 to 70rpm
Time Range	1 min to 19h59min
Timer Indicator	LCD
Voltage	100 to 240V, 50/60Hz
Weight	9kg
Working Temperature	5 to 40?,



E. Cherry St. Springfield MO 65802, USA
Email: info@labomate.com | Website: www.labomate.com