



Horizontal Laminar flow cabinet TRHL-601

www.labomate.com | info@labomate.com

Description

Horizontal Laminar flow cabinet TRHL-601 is a local purification unit used in a dust-free and aseptic clean environment. A similar enclosure creates a particle-free working environment by passing air through a filtration system. It comes with an easy-to-use quasi-glass damper. The Specification of the ultraviolet lamp is 1/10 W. It provides in a small and exquisite manner. It is presented with the air supply mode and supplies through both horizontal and vertical manner.

Features:

- Cold-rolled plate welding equipped throughout the equipment
- Comes with a stainless steel working area It is presented with a HEPA filter
- Built with a glass sliding door, and with a UV lamp and fluorescent lamp
- The surface electrostatically sprayed
- The air supply mode into the vertical and horizontal air supply
- Controlled by a simple to use quasi-closed glass damper
- It is small and exquisite
- It can operate freely on the general workbench, making it ideal for use in small studios
- A remote switch with fast controls the fan system

Specifications :

| | |
|--|---|
| Average Wind Speed | 0.25 to 0.45m/s (Fast and slow) |
| Cleanliness Level | Class 100@?0.5?M |
| High-Efficiency Filter Specification And Quantity | 475×410×38×1 |
| Illuminance | ?300Lx |
| Noise | ?62dB(A) |
| Number Of Colonies | ?0.5pcs/dish hour (?90mm culture plate) |
| Overall Dimension W×D×H | 650×530×850 mm |
| Power Supply | AC single-phase 220V/50Hz |
| Specification And Quantity Of Fluorescent Lamp/Ultraviolet Lamp | 5W×1/10W×1 |
| Vibration Half Peak | ?0.5?M(x, y, z-direction) |
| Working Area W1×D1×H1 | 490×490×490 mm |



E. Cherry St. Springfield MO 65802, USA
Email: info@labomate.com | Website: www.labomate.com